

Number #: 217-12

Name: Sachet Silk Sand Tinted Moisturizer

Category: Newsletters

Date: 09/21/2022



No	Phase	Trade Name	INCI	%
1	A	NOO Crystal	Octyldodecyl Oleate, Tocopheryl Acetate	7.35
2	A	PureSyn 6	Hydrogenated Polydecene	11.50
3	A	Vegetlight 1214LC	Coconut Alkanes (and) Coco-Caprylate/Caprate	2.50
4	A	Abil EM 180	Cetyl PEG/PPG-10/1 Dimethicone	5.00
5	A	Isolan GPS	Polyglyceryl-4 Diisostearate/Polyhydroxystearate/Sebacate	3.00
6	A	Bentone Gel ISD V	Isododecane (and) Disteardimonium Hectorite (and) Propylene Carbonate	5.00
7	B	Sachet Silk Sand	Synthetic Flurphlogopite, TiO2, Iron Oxides	6.00
8	C	DI Water	Water	50.15
9	C	Zemea® Propanediol	Propanediol	4.00
10	C	Glycerin 99.7% USP	Glycerin	3.00
11	C	Sodium Chloride	Sodium Chloride	0.75
12	D	SanSilica 610 AS	Silica, TES	1.00
13	D	Jeecide Phenoxy	Phenoxyethanol	0.75
Total				100%
Procedure	Heat and mix phase A using a homogenizer at 1500 rpm until Bentone Gel is solubilized. Heat to 45C. Add phase B, continue mixing until mixture is homogenous. In a separate beaker, heat and mix phase C to 45C until mixture is homogeneous. Under homogenizer, add phase C to phase A+B and mix at 2500 rpm , slowly increasing speed to 3000 rpm. Continue mixing under homogenizer for 3-5 minutes. Remove from homogenizer and mix under propeller, without heat. Add phase D and cool to room temperature. Fill into desired components.			

The information provided is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Sandream Specialties LLC. Customers should utilize formulations provided as a guide and perform in-house stability, micro and other necessary testing.